

PROCESS DEVELOPMENT FOR HIGH BLAST PAX EXPLOSIVES AT HOLSTON
ARMY AMMUNITION PLANT

Ms. Wendy Balas
TACOM-ARDEC
Picatinny Arsenal
Picatinny NJ 07806
Phone: 973-724-4919
Email: brooke.jones@baesystems.com

Thermobaric and metal accelerating explosives belong to a class of fuel-rich products that release energy over a longer period of time than conventional explosives formulations. When detonated, thermobaric explosives typically exhibit higher sustained blast pressures and increased lethality in confined spaces such as structures, tunnels and underground facilities. As a result, various Thermobaric explosive formulations, including PAX-3 and PAX-28, have been developed and evaluated in a number of submunition, projectile, and warhead systems. Additional formulations are being developed, utilizing non-traditional ingredients; that optimize IM properties while increasing impulse and duration.

Thermobaric explosives are typically supplied as a molding powder that can be pressed directly into a warhead. Traditionally, molding powders have been produced by a very economical a water-slurry process. However, a specific issue associated with the production of these Thermobaric explosive powders made from the traditional, low-cost water slurry method is the oxidation of Aluminum and other metals of interest in water. A “water replacement” fluid has been used as a substitute for water in the traditional water-slurry processing methods. This fluid allows the conventional solvent / anti-solvent coating process to be carried out in the absence of water, and hence eliminates the undesired water-Aluminum reaction.

This paper details the development and approach taken for the targeted Thermobaric formulations with a summary of the process utilized at HSAAP, laboratory experimental data, production scale-up data, and performance test results. IM testing data on the various Thermobaric formulations will be presented along with production cost of the Thermobaric materials produced.